

Temperature Resistance

- Temperature range from -10°C to +60°C
- The temperature at which the glue still adheres strongly depends on the surface, the humidity and the applied load

Application/Connection

- Use at room temperature 20°C (+/-5°C)
- Tape with glue and substrate must be at room temperature
- Press firmly together when gluing
- Maximum adherence after 48 hours at room temperature
- Under constant tension or pressure, the glue tends to displace slightly when used with certain fabrics
- The glue is not suitable for reuse

Surface

- Must be free of oil, dirt, dust, moisture, loose particles, monomeric plasticizers, silicones, flaking paint or coating
- Should not be too uneven, fragile, soft or unstable
- Should be suitable for the application of glue
- Should permit good bonding with adhesives, like most metals, wood, ceramics, stone, paper, cardboard, certain fabrics, various hard plastics and foams

Storage/Shelf Life

- In a dry, dark, dust-free and well ventilated room
- At a constant temperature of approx. 20°C (+/-5°C)
- Shelf life with correct storage: 12 months

User Tests/Warranty

- The above information is only for general guidance
- Based on their own tests, users should decide for themselves on the applicability of the fastening

General Instructions for Use

- Do not strain the self-adhesive tape within the first 24 hours after fastening
- Minimum recommended bonding temperature > 10°C
- Degrease the surface, e.g. with alcohol or spirit. The surface must be free of grease, moisture, dust, silicones, etc.
- Remove the protective paper and press the tape firmly in place. Pay particular attention to corners and edges!
- Bonding time: at least 1 hour at room temperature